

Fall arrest system, Wall support

Fall arrest system

The perfect protection for working at height

NEW
to our product range



The instructions for use and warnings must be observed before using the fall protection!

Art. no.	Material	Weight [kg]	Load bearing capacity [kg]	PU
800379	Polyester, nylon	5,5	100	1

Advantages

- Karabiner: static load capacity of 25 kN
- Full body harness: in accordance with EN 353-2, the minimum load-bearing capacity is 22 kN
- No jerky deceleration due to energy absorber
- Easy to detach following use
- Guided fall arrester with fasteners (removable)

Certifications

- Full body harness in accordance with EN 361
- Karabiner in accordance with EN 362:2004
- Rope in accordance with EN 353-2:2002
- Fall arrest device in accordance with EN 358:2001 / EN 365:2005

Description

The fall protection consists of a safety harness, a rope and a fall protection device with a connector. There is a carabiner at the end of the 15-metre-long rope and another one at the connector for fastening purposes. Standard-compliant equipment is particularly important, especially when working at height (on buildings, for example). It can prevent users from potentially falling from height and therefore a variety of injuries.

Wall support

Provides support during the installation of prefabricated walls, galvanised

Art. no.	Length [mm]	Angle of inclination	PU
803572	1600 - 3000	Max. 45°	1



Adjustment range of 160–300 cm

- Basic adjustment via 13 stop positions at intervals of 10,6 cm
- Fine adjustment with an adjustment range of 19 cm

Advantages

- Universal application
- Easy operation
- Fast assembly
- Almost no force needed from the user
- Very secure and sturdy
- Saves time

Makes the assembly of prefabricated walls significantly easier

Thanks to their high load-bearing capacity, the Eurotec wall supports can support walls until they are fully assembled without any problems and therefore take the place of many helping hands. A locking pin system allows especially quick and easy adjustment of the wall support's height. Subsequent fine adjustment is also possible using threaded rods.

Protective helmet (EN 397)

Perfect protection for work at a height and at ground level

Protective helmet



Art. no.	Head circumference [cm]	Total weight [g]	PU
800397/Black	51 - 62	375	1
800398/White	51 - 62	375	1
800399/Pink	51 - 62	375	1

Advantages and properties

- Optimum protection for work at a height and at ground level
- Control dial system allows adjustment to head size
→ Adjustable head size from 51 to 62 cm
- Efficient ventilation system thanks to 10 ventilation slots
- Four-point nylon chinstrap
- Lightweight and therefore very comfortable to wear
- Certified according to EN 397



Quick and easy control dial system for a perfect fit on the head



The ventilation system provides a pleasant cooling effect

